

iX Series

Compact indoor loudspeaker

Two way coaxial, bass reflex
1x8" ventilated cone driver
1" HF driver

Features

Small size
Natural or black wood finish
Wide conical dispersion
Sound clarity & reproduction accuracy

Applications

High class sound system
Distributed sound
Fixed installation, Monitoring

Specifications

60Hz - 20kHz @ -10dB
126 dB SPL Max @ 1m
100° x 100°
200 W AES - 8 ohms

Mono-amplification mode
IX8 M2-W white version

The APG iX8 M2 speaker is a two way wideband speaker developed for high quality fixed installations. It features a specific 8" cone driver with a coaxial dome tweeter.

The iX8 M2 is characterized by an extended bandwidth in the low frequency and offers precision and finesse of sound reproduction in Medium and High frequencies.

The coaxial mounting offers a perfect acoustic dispersion with a homogenous dispersion covering of 100°.

The T50 and T100 options comprise a 50W or 100W additional transformer for 70V-100V line cabling.

iX8 M2



iX8 M2 speaker

The iX8 M2 is a compact speaker offering studio monitor reproduction quality, intended for small and medium size indoor sound systems as well as for additional distributed sound in large installations.

Taking advantage of its compactness and its wide acoustical coverage, the iX8 M2 produces a clear and consistent sound while being very discreet. The two very high standard finishes offer the possibility of blending them in any modern design environment.


The iX8 M2 can be installed in many ways, wall, ceiling or truss-mounted via its specific rotating lyre bracket (option IX8BV/IX8BH), or simply put on a shelf. When used in full range mode, the iX8 M2 is ideal for conference applications, background music or as additional satellites for large P.A. system.

Combined with APG's subwoofers, the iX8 M2 constitute a very nice surround system ideal for background music applications in high class restaurants, cabarets or private clubs. It is also suitable for clubs, lounges and small dancing areas.

APG

iX8 M2

Technical Specifications



Features

Description	Compact indoor loudspeaker
Usable bandwidth (± 10 dB)	60 Hz - 20 kHz
SPL max @1m	126 dB SPL (1)
Nominal directivity ($H^\circ \times V^\circ$)	100° x 100° (2)
Nominal impedance	8 ohm

Components

Transducers	1 x 8" coaxial 1 x 1" HF ND driver
Topology	Coaxial - APG NDB Baffle
Type of load	Bass reflex
Way and amplification section	2 way, mono amplified

Power

AES	200 W (3)
Maximum power handling	800 W (4)

Construction

Cabinet / Painting	12 mm Finnish Birch plywood / Black impact resistant aquarethane
Dimensions H,W,D (mm)	10,9" x 16,1" x 9,1" (279 x 410 x 232 mm)
Weight (kg)	24 lb (11,1 kg)
Connectors	2 x Speakon NL4MP (5)
Handles	-
Front face	Acoustically transparent perforated steel, black acoustic tissue
Fittings	Insert M10 K&M 24521-000-55
Color	Black RAL 9005
IP	43

Options & Accessories

IX8BH	Horizontal lyre bracket for iX8 speakers (6)
IX8BHW	Horizontal lyre bracket for iX8W speakers (white version) (6)
IX8BHCOL	Horizontal lyre bracket for iX8 speakers (RAL version)
iX8BV	Vertical lyre bracket for iX8 speakers
iX8BVW	Vertical lyre bracket for iX8W speakers (white version)
iX8BVCOL	Vertical lyre bracket for iX8 speakers (RAL version)
CM-P	Phoenix connector kit
T100	Line transformer 70V / 100V, 100W

Electronics

Amplifiers	DA8, DA12 / DA14, DA2.8, DA6
------------	------------------------------

- (1) Peak level @ 1m AES2-2012 2msr using 12dB crest factor pink noise with APG preset
- (2) Nominal directivity @-6dB
- (3) Continuous power according to AES2-2012 in DCR
- (4) Peak power according to AES2-2012 in DCR
- (5) The 4 pins Speakon connectors are wired 1+, 1- in Lo/LoMid and 2+, 2- in Mid/Hi.
- (6) IX8BV / IX8BH is a steel bracket allowing installation of speakers on either wall or ceiling with angle adjustment.

5 YEARS WARRANTY *A five years warranty covers passive filters, transducers and compression drivers. The warranty does not cover cosmetic damages and damages due to misuse, improper installation, or damages caused by alterations.

Diffusion : July 2023 / DOP_1813_A

APG has a comprehensive research and development policy for the continual improvement of its products and service.

Due to this, new materials, manufacturing methods and technological changes may be introduced without prior notice. As a result, an APG product can differ from its published description in certain areas. However, unless otherwise indicated, its characteristics will always equal or better the published specifications.

APG

ARBANE GROUPE - 8 Rue Johannes Gutenberg 44340 BOUGUENAI - FRANCE
Tel. : +33 (0)2 40 46 66 64 - e.mail : contact@apg.audio - www.apg.audio

arbane
groupe